



MAINERO

DRY GRAIN BAGGER
MAINERO

 **2235**

www.mainero.com

Filling Tunnel	
Type:	Oblong or flattened.
Admitted bag size:	9 feet (2,74 m) - 60 and 75 meters
Bag mounting:	By means of retractable support with winch and hanger.
Materials to be bagged	All kinds of dry grains.
Transport position	Identical to work. Does not require additional elements Optional: set of wheel hubs, tongue and lights for end transport.
Working tongue	Foldable for end or truck transport.
Tractor requirement	
Minimum power:	45 CV (din)
Power take off:	540 RPM
Hydraulic system:	One double-acting hydraulic cylinder outlet.
Drive	Protected PTO shaft.
Safety system:	Torque limiter with shear bolt.
Brake system	Disk brake on both wheels. Adjustable braking by manual operating pump. Indicating manometer.
Wheel axle	Adjustable by agricultural type hydraulic cylinder (3" or 3½" x 8").
Feed	High capacity auger (more than 250 ton/hour).
Auger diameter:	450 mm
Bag retention	With encircling elastic harness.
Tires	7.00 - 15 - 8 ply - quantity 2
Total weight	1250 Kgs

Loader accessory for nozzle	
Auger diameter	260 mm
Drive	By hydraulic motor driven from the auxiliary hydraulic distributor of the tractor. Bypass valve let stop the loader drive without having to climb the tractor.
Required hydraulic system	Flow: 80 l/min. - pressure: 120 kg/cm3. Two outputs for double-acting hydraulic cylinders
Transport capacity	60 to 80 ton/hour*
Discharge hopper	Mobile to facilitate the approach of the truck and the transport of the accessory.
Wheel axle	Adjustable position by manual registration (work-transport)
Tires	6.40 x 13 - 4ply - quantity 2
Total weight	380 Kg
Loader accessory for dump trucks	
Auger Diameter	260 mm
Drive	By hydraulic motor driven from the auxiliary hydraulic distributor of the tractor. Bypass valve let stop the charger drive without having to climb the tractor.
Required hydraulic system	Flow: 80 l/min. - pressure: 120 kg/cm3. Two outputs for double-acting hydraulic cylinders.
Transport capacity	60 to 80 ton/hour*
Reception or Charge hopper	2,6 m wide. Foot support with rotating wheel that facilitates its hook for transport.
Wheel axle	Adjustable position by manual registration (work-transport)
Tires	6.40 x 13 - 4 ply - quantity 2
Total weight	530 Kg

* Variable according to type and grain condition; characteristics and performance of the hydraulic system of the tractor. The Company reserves the right to make changes without prior notice.

