



MAINERO



MIXER-FEEDER
MAINERO



www.mainero.com

Load volume:	8,5 m3.
Maximum load capacity:	3.500 Kg*
Tractor requirement	Minimum power: 60 CV (DIN)
Power take off:	540 RPM - 6 spline
Hydraulic group:	2 Outputs for double effect cylinders for: - Height and drive of unload augers. - Discharge gate opening and closing.
Drive:	Protected PTO shaft. Reducer group of gears and roller chains.
Safety system:	Fuse overload limiter.
Mixing system:	3 helical augers.
Mixing time:	2 to 4 minutes
Discharge	Type: By augers conveyor (quantity 2).
Drive:	Mechanic, automatic clutch.
Discharge gate opening:	From the tractor hydraulic distributor.
Magnetic plates:	Optional Equipment.
Discharge time:	Adjustable. Minimum 2 to 4 minutes.
Programmable electronic scale:	Optional equipment.
Admitted materials	Concentrated and dry by-products, corn and sorghum silage. Wet grain, fine chopped pasture silage, etc. as complement of a ration. Ground hay.
Wheel axle:	A wheel axle with adjustable simple wheel in three positions.
tires:	High flotation. Size 400/55 - 22.5 (quantity 2).
Optional wheel axle:	Independent adjustable rockers in three positions. Tires 10.00 x 16 - 10 ply (quantity 4)

General dimensions	Single axle	Rocker Axle
Total length (A):	5.168 mm	
Chamber length (B):	3.700 mm	
Chamber clearance (C):	1.000 mm	
Loading height (D):	2.656 mm	2.610 mm
Hopper width (E):	2.097 mm	
Distance from discharge wheel to tire (F):	667 mm	828 mm
Discharge minimum height (G):	841 mm	795 mm
Discharge height (G):	1.277 mm	1.231 mm
Total width (H):	2.900 mm	
Wheelbase (I):	1.808 mm	1.652 mm
Total weight:	2.850 kg	2.950 Kg

* Variable according to mix materials.
The Company reserves the right to make changes without prior notice.

