



MAINERO



MAINERO
ROW-INDEPENDENT
SUNFLOWER HEADER




www.mainero.com

Working widths		41 ft (12.6 m)	45 ft (13.65 m)
Pans		Weldless stainless steel. Foldable for transport purposes.	
Width:		8 1/3 in (213 mm)	
Passageway clearance:		Adjustable - excentric rod.	
Length:		6'3" in (1.900 mm)	
Pans prop:		Adjustable length pipe.	
Sickle bar	Type/make:	Modular, in sections / Schumacher.	
Drive/make:		Gearbox, V belt driven. Schumacher.	
Cutting knives:		3 per pan passageway.	
Sickle guards:		Standard -not sunflower special- long ones. Schumacher.	
Speed:		380 strokes/minute	
Reel:	Type:	Tube type	
Fingers:		3 per cutting line. Detachable - Adjustable	
Reel-Shield set adjustment:		Simultaneous. Hydraulic cylinders.	
Drive:		Hydraulic motor. Variable speed.	
Shield:	Type:	Stainless steel made. Wrap-around design. Pivoting arm shared with reel.	
Reel-Shield set adjustment:		Simultaneous. Hydraulic cylinders.	
Shield adjustment:		Mechanical slide fasteners.	
Stalk puller roll:	Type:	Modular, in sections with 4 bolted serrated lines.	
Mounting:		Sealed ball bearings.	
Location:		Between sickle-bar and pan props.	
Speed:		360 rpm	
Crossauger:	Type:	Independent crossauger.	
Mounting:		Hexagon shafts on sealed bearings on the sides and on drive gearbox in the center.	
Drive:		Center drive. Belt driven oil bath gearbox.	
Speed:		110 rpm	
Main Center Drive:		60° free rotation PTO shaft. Twin Poly V belt.	
Dimensions:	Transport width (A):	7,55 ft (2,300 mm)	
Transport height (B):		7,55 ft (2,300 mm)	
Transport length (C):		48,72 ft (14,850 mm)	52,16 ft (15,900 mm)
Working width (D):		41,34 ft (12,600 mm)	44,78 ft (13,650 mm)
Working length (E):		9,84 ft (3,000 mm)	
Weight:		8,267 lb (3,750 kg)	8,818 lb (4,000 kg)

Specifications and design subject to change without notice

WORKING



TRANSPORT

